# pyronics



### PYR-FA-CHA-XHS

ADDRESSABLE SOUNDER WITH BEACON

The PYR-FA-CHA-XHS is an addressable and intelligent sounder beacon with an internal microprocessor supporting two-wire advanced communication and electronic coding. The sounder beacon communicates with the fire alarm control panel in real-time the device status as well as receives and executes control commands from the fire alarm control panel. The sounder beacon will give a harsh audible and visual alarm signal for evacuation in case of confirmed detection.

### **KEY FEATURES**

- Modern Design and Feel
- Produces Audible and Visual Alarm
- Electronic Addressing via Handheld Programmer
- Polarity Insensitive for Ease of Installation and Maintenance
- 3 Year Warranty



### **SPECIFICATIONS**

#### **GENERAL**

Technology Microprocessor Based Addressing Software Addressing Wiring 2 Wire (Polarity Insensitive)

Base Clips Mount Base

#### PERFORMANCE

Flash Color Flash Rate 1 to 2 Hz **Sound Output** 85 dB @ 1 Meter **Beacon Output** 75 Candela Mounting Surface **EMI Protection** Yes

#### **ELECTRICAL**

Operating Voltage 24 V (Pulse Modulation)

Standby Current 2 mA **Alarm Current** 8 mA

#### **MECHANICAL**

Material Flame Retardant High Impact

**Durable Engineered ABS Polymer** 

**Dimensions**  $\phi$  100 mm x 100.5 mm

(Diameter x Height)

Weight 236 gm (With Base)

#### ENVIRONMENTAL

Indoor / Outdoor with Back Box Application

IP21C for Indoor MCPs Ingress Protection

IP66 for Outdoor MCPs

-10 °C to +55 °C **Operating Temperature** 

-20 °C to +60 °C Storage Temperature

0 to 95% (Relative Humidity) Humidity

#### REGULATORY


Certification LPCB according to EN54-3


Declaration CE






## **DIMENSIONS**





### **WIRING**





# **ORDERING INFORMATION**

Model	Description
PYR-FA-CHA-HS	INDOOR ADDRESSABLE SOUNDER WITH BEACON
PYR-FA-CHA-OHS	OUTDOOR ADDRESSABLE SOUNDER WITH BEACON





Email info@pyronics.us
Website www.Pyronics.us

